

Safety Data Sheet
For Compliance with OSHA 29 CFR 1910.1200 and ANSI Z400.1-1998

1. Product and Company Identification		
Product Name	PolyColor Dye – Light Green	
Manufacturer's name	Horizons Incorporated	
Address	18531 South Miles Road Cleveland, Ohio 44128	
Emergency Telephone Number	(216) 475-0555	
Information Telephone Number	(216) 475-0555	

2. Hazards Identification				
GHS Classification				
H227	Flammable liquid – Category 4			
H303	Acute toxicity, Oral – Category 5			
H333	Acute toxicity, Inhalation – Category 5			
H313	Acute toxicity, Dermal – Category 5			
H318	Skin corrosion/irritation – Category 2			
H320	Serious eye damage/eye irritation – Category 2B			
GHS Label Elements				
Hazard Pictogram				
Signal Word	Warning			
Hazard Statements				
H227	Combustible liquid			
H303	May be harmful if swallowed			
H313	May be harmful in contact with skin			
H333	May be harmful if inhaled			
H315	Causes skin irritation			
H320	Causes eye irritation			
Precautionary Statements				
P210	Keep away from heat, hot surfaces, sparks, open flames, and other			
	ignition sources. No smoking			
P264	Wash thoroughly after handling			
P280	Wear protective gloves, protective clothing, and eye protection			
P302+P352	IF ON SKIN: wash with plenty of water			
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove			
	contact lenses, if present and easy to do. Continue rinsing			
P332+P337+P313	If skin or eye irritation occurs or persists: Get medical advice/attention			
P312	Call a poison center/doctor if you feel unwell			
P362+P364	Take off contaminated clothing and wash before reuse			
P403	Store in a well-ventilated place			

3. Composition/Information on Ingredients			
Components/ Materials CAS Number %			
Butyl Lactate	138-22-7	85	
Solvent Blue 70	Not available	8	
Solvent Yellow 83:1	Not available	7	
Chromium III (as an integral part of the dye molecule)	7440-47-3	0.35	
Copper (as an integral part of the dye molecule)	7440-50-8	<0.1	

4. First Aid Measur	res
Inhalation	Promptly remove to fresh air. If breathing is stopped or irregular, administer artificial respiration. Get medical attention immediately.
Skin Contact	Wash affected area with soap & water after contact. Rinse immediately with plenty of water for at least 15 minutes Remove & wash contaminated clothing before reuse. If irritation develops, get medical attention.
Eye Contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation develops & persists.
Ingestion	Rinse mouth with water. DO NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

5. Fire Fighting Measures			
Flammable Properties		Flash point – >156°F (69°C) TCC	
Flammable Limits			
	Lower Flammable Limit	Not available	
	Upper Flammable Limit	Not available	
Hazardous Co	mbustion Products	Carbon monoxide, Carbon dioxide, nitrogen oxides, & chromium oxides.	
Unusual Fire/Explosion Hazards		Combustion products may be irritating to the skin, eyes, nose, and respiratory system.	
Extinguishing Media		Foam. Carbon Dioxide (CO <sub>2</sub> ). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
Special Firefighting Procedures		Wear self-contained breathing apparatus & protective clothing to prevent contact with skin and eyes. Cool containers with water spray. Fire or intense heat may cause violent rupture of packages.	

6. Accidental Release Measures			
Small Spill	Absorb spill with an inert material and place in a chemical waste container		
Large Spill	Remove all sources of ignition. Ventilate area. Contain spilled liquid with sand or earth. Absorb spill with an inert material and shovel into a chemical waste container. Prevent runoff from entering into sewers and ditches which lead into natural waterways.		

7. Handling and Storage		
Handling	Avoid contact with eyes and clothing. Keep container closed. Use only in a well ventilated area. Wash thoroughly after handling. Avoid prolonged or repeated breathing of mists and vapors. Avoid prolonged or repeated contact with skin.	
Storage	Store between 65-85°F. Keep containers sealed when not in use.	

8. Exposure Control/Personal Protection				
Exposure Limits				
Chemical Name	CAS No.	OSHA	ACGIH	NIOSH
Butyl Lactate	138-22-7	25 mg/m3 TWA	5 ppm TWA	5 ppm IDLH
Solvent Blue 70		ND	ND	ND
Solvent Yellow 83:1		ND	ND	ND
Chromium III	7440-47-3	0.5mg/m3 TWA	0.5 mg/m3 TWA	ND
compounds		_	_	
ND – Not Determined				
		rations below the exposure limits. Use only with all exhaust ventilation may be necessary. Keep ever possible.		
Respiratory Protection	When respiratory protection is required, use a NIOSH approved air- purifying respirator equipped with an organic vapor canister. For emergency and other conditions where exposure limits may be greatly exceeded, use an approved positive-pressure, self-contained breathing apparatus or positive-pressure air line with auxiliary self-contained air supply.		or canister. For limits may be greatly elf-contained breathing ary self-contained air	
Skin Protection	Skin Protection Wear protective gloves and clothing. Use solvent-resistant apron 8 if needed.		-resistant apron & boots,	
Eye Protection	Eye Protection Use safety glasses with side shields or, preferably, chemical goggles.			y, chemical goggles.

9. Physical and Chemical Properties		
Boiling Point	367°F (186°C)	
Specific Gravity	1.01	
% Volatiles	85%	
Solubility in Water	Slightly soluble (3.4ml/100ml)	
pH	No information available	
Odor	Mild, characteristic odor	
Form	Liquid	
Color	Green	
VOC	7.15 lbs/gal coating	

10. Stability and Reactivity		
Chemical Stability	Stable under normal storage conditions	
Conditions to Avoid	Keep product away from heat, sparks, static electricity, and open flame.	
Incompatibility	Strong bases. Strong oxidizing agents.	
Hazardous Decomposition Products	Burning can produce carbon monoxide, carbon dioxide, nitrogen	
	oxides, & chromium oxides when heated to decomposition.	
Hazardous Polymerization	Will not occur	

11. Toxicological Information		
Results of component toxicity test performed:		
Data for Butyl Lactate	Acute Toxicity Data: Oral rat LD50: >5000 mg/kg;	
(CAS 138-22-7)	Subcutaneous rat LD50: 12000 mg/kg;	
	Skin rabbit LD50: >5000 mg/kg;	
	Draize test, rabbit, skin: 500 mg/24H Moderate	
	Inhalation, rat LC50:>5140 mg/kg	
Data for Solvent Blue 70	Acute Toxicity Data: Oral rat LD50: >5000 mg/kg;	
Data for Solvent Yellow 83:1	Acute Toxicity Data: Oral rat LD50: >2000 mg/kg.	

12. Ecological Information			
The following properties are ESTIMATED from the components of the preparations.			
Potential Toxicity:			
Toxicity to Danio rerio (LC50): 75 mg/L /96 Hr			
Toxicity to Daphnia magna (EC50): 320 mg/L /48Hr			
Persistence and degradability		ND	
Chemical Oxygen Demand (COD)		1.97lb O <sub>2</sub> /lb	
Biochemical Oxygen Demand (BOD)		ND	
Chemical Fate Information		ND	

**13. Disposal Considerations**This product contains chromium predominantly in the trivalent state. Wastes containing chromium may be D007 RCRA

hazardous wastes per 40 CFR261.24.
Liquid material should be disposed as flammable waste. Note that Federal, State and local laws governing disposal of materials can differ. Ensure proper disposal compliance with proper authorities before disposal.
Contact a licensed professional waste disposal service to dispose of large quantities of this material

14. Transport Information	
Proper Shipping Name	Combustible Liquid, N.O.S.
UN No.	NA1993
IATA Class	Not Regulated
Packing Group	

15. Regulatory Information	
U.S. Federal Regulations	
TSCA Section 8 (b) Inventory	All components are listed on the TSCA Chemical Inventory
OSHA	Hazardous by definition of Hazard Communications Standard (29CFR1910.1200)
SARA Hazard Category	
SARA 302 Components	No listed components
SARA 313 Components	Chromium III compounds.
SARA 311/312 Hazards	Acute Health Hazard, Chronic Health Hazard, Fire Hazard
Clean Water Act	Contains priority pollutant chromium at concentrations >0.1%
CERCLA	Chromium, RQ 5000pounds

State Regulations		
Massachusetts Right To Know	Butyl Lactate	
Components	,	
Pennsylvania Right To Know	Butyl Lactate	
Components		
New Jersey Right To Know	Butyl Lactate	
Components	·	
California Proposition 65 Components	This product does not contain any chemical known to the State of	
	California to cause cancer or reproductive harm.	
	,	

The information in this material safety data sheet should be provided to all who will use, handle, store, transport, or otherwise be exposed to this product. This information has been prepared for the guidance of plant engineering, operations & management, and for persons working with or handling this product. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions but does not purport to be all inclusive. Horizons Incorporated shall not be held liable for any damage resulting from handling or from contact with the above product.