

Safety Data SheetFor Compliance with OSHA 29 CFR 1910.1200 and ANSI Z400.1-1998

1. Product and Company Identification		
Product Name	PolyColor Dye – UC Blue	
Manufacturer's name	Horizons Incorporated	
Address	18531 South Miles Road Cleveland, Ohio 44128	
Emergency Telephone Number	(216) 475-0555	
Information Telephone Number	(216) 475-0555	

2. Hazards Identification			
GHS Classification			
H227	Flammable liquid – Category 4		
H303	Acute toxicity, Oral – Category 5		
H333	Acute toxicity, Inhalation – Category 5		
H313	Acute toxicity, Dermal – Category 5		
H318	Skin corrosion/irritation – Category 2		
H320	Serious eye damage/eye irritation – Category 2B		
GHS Label Elements			
Hazard Pictogram	<u>(1)</u>		
Signal Word	Warning		
Hazard Statements			
H227	Combustible liquid		
H303	May be harmful if swallowed		
H313	May be harmful in contact with skin		
H333	May be harmful if inhaled		
H315	Causes skin irritation		
H320	Causes eye irritation		
Precautionary Statements			
P210	Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking		
P264	Wash thoroughly after handling		
P280	Wear protective gloves, protective clothing, and eye protection		
P302+P352	IF ON SKIN: wash with plenty of water		
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing		
P332+P337+P313	If skin or eye irritation occurs or persists: Get medical advice/attention		
P312	Call a poison center/doctor if you feel unwell		
P362+P364	Take off contaminated clothing and wash before reuse		
P403	Store in a well-ventilated place		

3. Composition/Information on Ingredients			
Components/ Materials CAS Number %			
Butyl Lactate	138-22-7	88	
Solvent Blue 45	Not available	10	
Solvent Black 3	Not available	1	
Solvent Red 119	Not available	1	
Chromium III (as an integral part of the dye molecule)	7440-47-3	<0.05	

4. First Aid Measures	
Inhalation	Promptly remove to fresh air. If breathing is stopped or irregular, administer artificial respiration. Get medical attention immediately.
Skin Contact	Wash affected area with soap & water after contact. Rinse immediately with plenty of water for at least 15 minutes Remove & wash contaminated clothing before reuse. If irritation develops, get medical attention.
Eye Contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation develops & persists.
Ingestion	Rinse mouth with water. DO NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

5. Fire Fighting Measures		
Flammable Properties	Flash point – >156°F (69°C) TCC	
Flammable Limits		
Lower Flammable Limit	Not available	
Upper Flammable Limit	Not available	
Hazardous Combustion Products	Carbon monoxide, Carbon dioxide, nitrogen oxides, sulfur dioxide, chromium oxides.	
Unusual Fire/Explosion Hazards	Combustion products may be irritating to the skin, eyes, nose, and respiratory system.	
Extinguishing Media	Foam. Carbon Dioxide (CO ₂). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
Special Firefighting Procedures	Wear self-contained breathing apparatus & protective clothing to prevent contact with skin and eyes. Cool containers with water spray. Fire or intense heat may cause violent rupture of packages.	

6. Accidental Release Measures		
Small Spill	Absorb spill with an inert material and place in a chemical waste container	
Large Spill	Remove all sources of ignition. Ventilate area. Contain spilled liquid with sand or earth. Absorb spill with an inert material and shovel into a chemical waste container. Prevent runoff from entering into sewers and ditches which lead into natural waterways.	

7. Handling and Storage		
Handling	Avoid contact with eyes and clothing. Keep container closed. Use only in a well ventilated area. Wash thoroughly after handling. Avoid prolonged or repeated breathing of mists and vapors. Avoid prolonged or repeated contact with skin.	
Storage	Store between 65-85°F. Keep containers sealed when not in use.	

8. Exposure Control/Personal Protection				
Exposure Limits				
Chemical Name	CAS No.	OSHA	ACGIH	NIOSH
Butyl Lactate	138-22-7	25 mg/m3 TWA	5 ppm TWA	5 ppm IDLH
Solvent Blue 45		ND	ND	ND
Solvent Black 3		ND	ND	ND
Solvent Red 119		ND	ND	ND
Chromium III	7440-47-3	0.5mg/m3 TWA	0.5 mg/m3 TWA	ND
compounds				
ND – Not Determined				ND – Not Determined
Engineering Controls		Control airborne concentrations below the exposure limits. Use only with adequate ventilation. Local exhaust ventilation may be necessary. Keep containers covered whenever possible.		ation may be
Respiratory Protection	n	When respiratory protection is required, use a NIOSH approved airpurifying respirator equipped with an organic vapor canister. For emergency and other conditions where exposure limits may be greatly exceeded, use an approved positive-pressure, self-contained breathing apparatus or positive-pressure air line with auxiliary self-contained air supply.		NIOSH approved air- apor canister. For are limits may be ressure, self-contained
Skin Protection		Wear protective gloves and clothing. Use solvent-resistant apron & boots, if needed.		
Eye Protection	ion Use safety glasses with side shields or, preferably, chemical goggles.			ably, chemical goggles.

9. Physical and Chemical Properties				
Boiling Point	367°F (186°C)			
Specific Gravity	1.00			
% Volatiles	88%	88%		
Solubility in Water	Slightly soluble (3.4ml/100ml)	Slightly soluble (3.4ml/100ml)		
рН	No information available	No information available		
Odor	Mild, characteristic odor	Mild, characteristic odor		
Form	Liquid			
Color	Blue	Blue		
VOC	7.33 lbs/gal coating	7.33 lbs/gal coating		

10. Stability and Reactivity		
Chemical Stability	Stable under normal storage conditions	
Conditions to Avoid	Keep product away from heat, sparks, static electricity, and open flame.	
Incompatibility	Strong bases. Strong oxidizing agents.	
Hazardous Decomposition Products	Burning can produce carbon monoxide, carbon dioxide, nitrogen oxides, chromium oxides& sulfur dioxide when heated to decomposition.	
Hazardous Polymerization	Will not occur	

11. Toxicological Information		
Results of component toxicity test performed:		
Data for Butyl Lactate	Acute Toxicity Data: Oral rat LD50: >5000 mg/kg;	
(CAS 138-22-7)	Subcutaneous rat LD50: 12000 mg/kg;	
·	Skin rabbit LD50: >5000 mg/kg;	
	Draize test, rabbit, skin: 500 mg/24H Moderate	
	Inhalation, rat LC50:>5140 mg/kg	
Data for Solvent Blue 45	Acute Toxicity Data: Oral rat LD50: >2000 mg/kg;	
	Dermal rat LD50: >2000 mg/kg.	
Data for Solvent Black 3	Acute Toxicity Data: Oral rat LD50: >2000 mg/kg.	
Data for Solvent Red 119 Acute Toxicity Data: Oral rat LD50: >10000 mg/kg.		

12. Ecological Information			
The following properties are ESTIMATED from the components of the preparations.			
Potential Toxicity:			
Toxicity to Danio rerio (LC50): 75 mg/L /96 Hr			
Toxicity to Daphnia magna (EC50): 320 mg/L /48Hr			
Persistence and degradability		ND	
Chemical Oxygen Demand (COD)		1.97lb O ₂ /lb	
Biochemical Oxygen Demand (BOD)		ND	
Chemical Fate Information		ND	

13. Disposal Considerations

This product contains chromium predominantly in the trivalent state. Wastes containing chromium may be D007 RCRA

hazardous wastes per 40 CFR261.24.
Liquid material should be disposed as flammable waste. Note that Federal, State and local laws governing disposal of materials can differ. Ensure proper disposal compliance with proper authorities before disposal.

Contact a licensed professional waste disposal service to dispose of large quantities of this material

14. Transport Information	
Proper Shipping Name	Combustible Liquid, N.O.S.
UN No.	NA1993
IATA Class	Not Regulated
Packing Group	III

15. Regulatory Information		
U.S. Federal Regulations		
TSCA Section 8 (b) Inventory	All components are listed on the TSCA Chemical Inventory	
OSHA	Hazardous by definition of Hazard Communications Standard (29CFR1910.1200)	
SARA Hazard Category		
SARA 302 Components	No listed components	
SARA 313 Components	Chromium III compounds.	
SARA 311/312 Hazards	Acute Health Hazard, Chronic Health Hazard, Fire Hazard	
Clean Water Act	Contains priority pollutant chromium at concentrations >0.1%	
CERCLA	Chromium, RQ 5000pounds	
State Regulations		
Massachusetts Right To Know	Butyl Lactate	
Components		
Pennsylvania Right To Know Components	Butyl Lactate	
New Jersey Right To Know Components	Butyl Lactate	
California Proposition 65 Components	This product does not contain any chemical known to the State of	
	California to cause cancer or reproductive harm.	

16. Other Information
HMIS
H-2
F – 2
R – 0
PPE – B

The information in this material safety data sheet should be provided to all who will use, handle, store, transport, or otherwise be exposed to this product. This information has been prepared for the guidance of plant engineering, operations & management, and for persons working with or handling this product. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions but does not purport to be all inclusive. Horizons Incorporated shall not be held liable for any damage resulting from handling or from contact with the above product.