

Safety Data SheetFor Compliance with OSHA 29 CFR 1910.1200 and ANSI Z400.1-1998

1. Product and Company Identification		
Product Name	PolyColor Screen Ink – UC Red	
Manufacturer's name	Horizons Incorporated	
Address	18531 South Miles Road Cleveland, Ohio 44128	
Emergency Telephone Number	(216) 475-0555	
Information Telephone Number	(216) 475-0555	

2. Hazards Identification			
GHS Classification			
H226	Flammable liquid – Category 3		
H302	Acute toxicity, Oral – Category 4		
H332	Acute toxicity, Inhalation – Category 4		
H312	Acute toxicity, Dermal – Category 4		
H315	Skin corrosion/irritation – Category 2		
H320	Serious eye damage/eye irritation – Category 2B		
H317	Skin sensitization – Category 1B		
GHS Label Elements	•		
Hazard Pictogram	\wedge		
Ç			
Signal Word	Danger		
Hazard Statements			
H226	Flammable liquid and vapor		
H302+H332	Harmful if swallowed or inhaled		
H312	Harmful in contact with skin		
H315	Causes skin irritation		
H320	Causes eye irritation		
H317	May cause an allergic skin reaction		
Precautionary Statements			
P210	Keep away from heat, hot surfaces, sparks, open flames, and other		
Bass	ignition sources. No smoking		
P233	Keep container tightly closed		
P280	Wear protective gloves/clothing and eye protection		
P264	Wash thoroughly after handling		
P270	Do not eat, drink, or smoke when using this product		
P261 P271	Avoid breathing fume, mists, & vapors		
P271 P272	Use only in a well-ventilated area Contaminated work clothing should not be allowed out of the workplace		
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing.		
P303+P301+P353	Rinse skin with water		
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove		
F303+F331+F336			
P333+P337+P313	contact lenses, if present and easy to do. Continue rinsing		
F333+F331+F313	If skin rash or eye irritation occurs or persists, get medical		
D201 - D220	advice/attention IF SWALLOWED: Rinse mouth.		
P301+P330 P304+P340	IF SWALLOWED: Rinse mouth. IF INHALED: Remove person to fresh air and keep comfortable for		
F3U4TF34U	breathing		
P362+P364	Take off contaminated clothing and wash before reuse		
P312	Call a poison center/doctor if you feel unwell		
P403+P235	Store in a well-ventilated place. Keep cool		
1 70011 200	Otoro in a won vontilated place. Neep cool		

3. Composition/Information on Ingredients			
Components/ Materials	CAS Number	%	
Diethylene Glycol Monobutyl Ether	112-34-5	<15	
Propylene Glycol Methyl Ether Acetate	108-65-6	<55	
Cyclohexanone	108-94-1	<8	
2-Butoxyethanol	111-76-2	10	
Solvent Red 119	Not available	6	
Solvent Blue 70	Not available	1	
Copper (as an integral part of the dye molecule)	7440-50-8	<0.05%	

4. First Aid Measu	ires
Inhalation	Promptly remove to fresh air. If breathing is difficult or irregular, give oxygen. If breathing is stopped, administer artificial respiration. Get medical attention immediately.
Skin Contact	Wash affected area with soap & water after contact. Rinse immediately with plenty of water for at least 15 minutes Remove & wash contaminated clothing before reuse. If irritation develops, get medical attention.
Eye Contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Keep eyes wide open while rinsing. Get medical attention if irritation develops & persists.
Ingestion	Rinse mouth with water. DO NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

5. Fire Fighting Measures		
Flammable Properties	Flash point – >111°F (44°C) TCC	
Flammable Limits		
Lower Flammable Limit	0.9 Vol%	
Upper Flammable Limit	24.6 Vol%	
Hazardous Combustion Products	May include but not limited to: Carbon monoxide, Carbon dioxide, Nitrogen oxides.	
Unusual Fire/Explosion Hazards	Combustion products may be irritating to the skin, eyes, nose, and respiratory system. Vapor may travel back to ignition source and flashback. Product may be sensitive to static discharge, which could result in fire or explosion.	
Extinguishing Media	Foam. Carbon Dioxide (CO ₂). Dry chemical. Water fog. Do not use direct water stream, which may spread fire. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
Special Firefighting Procedures	Wear self-contained breathing apparatus & protective clothing to prevent contact with skin and eyes. Cool containers with water spray. Fire or intense heat may cause violent rupture of packages.	

6. Accidental Release Measures		
Small Spill	Absorb spill with an inert material and place in a chemical waste container	
Large Spill	Remove all sources of ignition. Ventilate area. Contain spilled liquid with sand or earth. Absorb spill with an inert material and shovel into a chemical waste container. Prevent runoff from entering into sewers and ditches which lead into natural waterways. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.	

7. Handling and Storage		
Handling	Avoid contact with eyes and clothing. Keep container closed. Use only in a well ventilated area. Wash thoroughly after handling. Avoid prolonged or repeated breathing of mists and vapors. Avoid prolonged or repeated contact with skin. Keep away from ignition sources. Take measures to prevent build-up of electrostatic charge.	
Storage	Store between 65-85°F. Keep containers sealed when not in use.	

8. Exposure Co	ontrol/Perso	nal Protection		
Exposure Limits				
Chemical Name	CAS No.	OSHA	ACGIH	NIOSH
Diethylene Glycol Monobutyl Ether	112-34-5	ND	ND	ND
Propylene Glycol Methyl Ether Acetate	108-65-6	ND	ND	ND
Cyclohexanone	108-94-1	50 ppm TWA	20 ppm TWA (skin)	25 ppm TWA 700 ppm IDLH
2-Butoxyethanol	111-76-2	120 mg/m3 TWA	20 ppm TWA	700 ppm IDLH
Solvent Blue 70		ND	ND	ND
Solvent Red 119		ND	ND	ND
				ND – Not Determined
Engineering Controls		Control airborne concentrations below the exposure limits. Use only with adequate ventilation. Local exhaust ventilation may be necessary. Keep containers covered whenever possible. Where explosive mixtures may be present, equipment safe for such locations should be used.		ion may be necessary. here explosive mixtures ns should be used.
Respiratory Protection		When respiratory protection is required, use a NIOSH approved air- purifying respirator equipped with an organic vapor canister. For emergency and other conditions where exposure limits may be greatly exceeded, use an approved positive-pressure, self-contained breathing apparatus or positive-pressure air line with auxiliary self-contained air supply.		
Skin Protection		Wear protective gloves and clothing. Use of natural rubber (latex) gloves is NOT recommended. Use solvent-resistant apron & boots, if needed.		
Eye Protection		Use safety glasses with side shields or, preferably, chemical goggles. Contact lens use is not recommended.		

9. Physical and Chemical Properties		
Boiling Point	302°F - 446°F (150°C - 230°C)	
Specific Gravity	0.95	
% Volatiles	74%	
Solubility in Water	Insoluble	
рН	No information available	
Odor	Mild, ester-like odor	
Form	Liquid	
Color	Red	
VOC	5.86 lbs/gal coating (702 g/L)	

10. Stability and Reactivity	
Chemical Stability	Stable under normal storage conditions
Conditions to Avoid	Keep product away from heat, sparks, static electricity, and open flame.
Incompatibility	Strong acids. Strong bases. Strong oxidizing agents.
Hazardous Decomposition Products	Burning can produce carbon monoxide, carbon dioxide, & nitrogen
	oxides when heated to decomposition.
Hazardous Polymerization	Will not occur

11. Toxicological Information			
Results of component toxicity test performed:			
Data for Diethylene Glycol Monobutyl Ether (CAS 112-34-5)	Acute Toxicity Data: Oral rat LD50: >2000 mg/kg; Dermal rabbit LD50: >2000 mg/kg; Repeated Dose Toxicity: Causes haemolysis of red blood cells &/or anemia in animals, but not considered relevant to humans.		
Data for Propylene Glycol Methyl Ether Acetate (CAS 108-65-6)	Acute Toxicity Data: Oral rat LD50: 8532 mg/kg; Dermal rabbit LD50: >5000 mg/kg;		
Data for Cyclohexanone (CAS 108-94-1)	Acute Toxicity Data: Oral rat LD50: 1800 mg/kg; Oral mouse LD50: 1400 mg/kg; Dermal rabbit LD50: 1 ml/kg; Inhalation rat LC50: 8000 ppm/4H; Draize rabbit, eye: 20 mg, severe. ACGIH A3 – Confirmed animal carcinogen with unknown relevance to humans.		
Data for 2-Butoxyethanol (CAS 111-76-2)	Acute Toxicity Data: Oral rat LD50: 470 mg/kg; Skin rabbit LD50: 220 mg/kg; Inhalation rat LC50: 2.21 mg/L (4 hr)		
Data for Solvent Blue 70	Acute Toxicity Data: Oral rat LD50: >5000 mg/kg;		
Data for Solvent Red 119	Acute Toxicity Data: Oral rat LD50: >10000 mg/kg.		

12. Ecological Information

The following properties are ESTIMATED from the components of the preparations.			
Potential Toxicity:			
Toxicity to Salmo gairdneri (LC50): 100-180 mg/L /96 Hr			
Toxicity to Daphnia magna (EC50):	>100 mg/L /48 Hr		
Toxicity to D. subspicatus (IC50): > 100 mg/L 24 Hr			
Persistence and degradability		ND	
Chemical Oxygen Demand (COD)		ND	
Biochemical Oxygen Demand (BOD)		ND	
Chemical Fate Information		ND	

13. Disposal Considerations

Liquid material should be disposed as flammable waste. Note that Federal, State and local laws governing disposal of materials can differ. Ensure proper disposal compliance with proper authorities before disposal.

Contact a licensed professional waste disposal service to dispose of large quantities of this material

14. Transport Information		
Proper Shipping Name	Printing Ink	
UN No.	UN1210	
IATA Class	Class 3	
Packing Group	III	

In the U.S. & Canada, this material may be reclassified as a combustible liquid and is not regulated, via surface transportation, in containers less than 119 gallons or 450 liters [per 49 CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/Clear Language Part 1.33].

15. Regulatory Information		
U.S. Federal Regulations		
TSCA Section 8 (b) Inventory	All components are listed on the TSCA Chemical Inventory	
OSHA	Hazardous by definition of Hazard Communications Standard	
	(29CFR1910.1200)	
SARA Hazard Category		
SARA 302 Components	No listed components	
SARA 313 Components	Diethylene glycol monobutyl ether & 2-Butoxyethanol are subject to the	
	reporting requirements of Section 313 of SARA 313Title III and 40CFR.	
SARA 311/312 Hazards	Acute Health Hazard, Chronic Health Hazard, Fire Hazard	
Clean Air Act	Diethylene glycol monobutyl ether is listed as a hazardous air pollutant	
	(HAP).	
CERCLA	Cyclohexanone; 5000 lb final RQ.	
State Regulations		
Massachusetts Right To Know	2-Butoxyethanol, Cyclohexanone	
Components		
Pennsylvania Right To Know Components	2-Butoxyethanol, Cyclohexanone, Diethylene glycol monobutyl ether	
New Jersey Right To Know Components	2-Butoxyethanol, Cyclohexanone	
California Proposition 65 Components	This product does not contain any chemical known to the State of	
	California to cause cancer or reproductive harm.	

16. Other Information	
HMIS	
H – 2	
F-2	
R – 0	
PPE – B	

The information in this material safety data sheet should be provided to all who will use, handle, store, transport, or otherwise be exposed to this product. This information has been prepared for the guidance of plant engineering, operations & management, and for persons working with or handling this product. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions but does not purport to be all inclusive. Horizons Incorporated shall not be held liable for any damage resulting from handling or from contact with the above product.