

Safety Data Sheet

For Compliance with OSHA 29 CFR 1910.1200 and ANSI Z400.1-1998

1. Product and Company Identification		
Product Name	PolyColor Dye – Yellow	
Manufacturer's name	Horizons Incorporated	
Address	18531 South Miles Road Cleveland, Ohio 44128	
Emergency Telephone Number	(216) 475-0555	
Information Telephone Number	(216) 475-0555	

2. Hazards Identific	ation
GHS Classification	ation
H227	Flammable liquid – Category 4
H303	Acute toxicity, Oral – Category 5
H333	Acute toxicity, Inhalation – Category 5
H313	Acute toxicity, Dermal – Category 5
H318	Skin corrosion/irritation – Category 2
H320	Serious eye damage/eye irritation – Category 2B
GHS Label Elements	
Hazard Pictogram	
Signal Word	Warning
Hazard Statements	-
H227	Combustible liquid
H303	May be harmful if swallowed
H313	May be harmful in contact with skin
H333	May be harmful if inhaled
H315	Causes skin irritation
H320	Causes eye irritation
Precautionary Statements	
P210	Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking
P264	Wash thoroughly after handling
P280	Wear protective gloves, protective clothing, and eye protection
P302+P352	IF ON SKIN: wash with plenty of water
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing
P332+P337+P313	If skin or eye irritation occurs or persists: Get medical advice/attention
P312	Call a poison center/doctor if you feel unwell
P362+P364	Take off contaminated clothing and wash before reuse
P403	Store in a well-ventilated place

3. Composition/Information on Ingredients		
Components/ Materials	CAS Number	%
Butyl Lactate	138-22-7	85
Solvent Yellow 82	Not Available	15

4. First Aid Measu	ıres
Inhalation	Promptly remove to fresh air. If breathing is stopped or irregular, administer artificial respiration. Get medical attention immediately.
Skin Contact	Wash affected area with soap & water after contact. Rinse immediately with plenty of water for at least 15 minutes Remove & wash contaminated clothing before reuse. If irritation develops, get medical attention.
Eye Contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation develops & persists.
Ingestion	Rinse mouth with water. DO NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

5. Fire Fighting Measures		
Flammable Properties	Flash point – >156°F (69°C) TCC	
Flammable Limits		
Lower Flammable Limit	Not available	
Upper Flammable Limit	Not available	
Hazardous Combustion Products	Carbon monoxide, Carbon dioxide, nitrogen oxides.	
Unusual Fire/Explosion Hazards	Combustion products may be irritating to the skin, eyes, nose, and respiratory system.	
Extinguishing Media	Foam. Carbon Dioxide (CO ₂). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
Special Firefighting Procedures	Wear self-contained breathing apparatus & protective clothing to prevent contact with skin and eyes. Cool containers with water spray. Fire or intense heat may cause violent rupture of packages.	

6. Accidental Release Measures		
Small Spill	Absorb spill with an inert material and place in a chemical waste container.	
Large Spill	Remove all sources of ignition. Ventilate area. Contain spilled liquid with sand or earth. Absorb spill with an inert material and shovel into a chemical waste container. Prevent runoff from entering into sewers and ditches which lead into natural waterways.	

7. Handling and Storage		
Handling	Avoid contact with eyes and clothing. Keep container closed. Use only in a well ventilated area. Wash thoroughly after handling. Avoid prolonged or repeated breathing of mists and vapors. Avoid prolonged or repeated contact with skin.	
Storage	Store between 65-85°F. Keep containers sealed when not in use.	

8. Exposure C	ontrol/Pers	sonal Protection			
Exposure Limits					
Chemical Name	CAS No.	OSHA	ACGIH	NIOSH	
Butyl Lactate	138-22-7	25 mg/m3 TWA	5 ppm TWA	5 ppm IDLH	
Solvent Yellow 82		ND	ND	ND	
				ND – Not Determined	
Engineering Controls		Control airborne concent	trations below the expos	sure limits. Use only	
		with adequate ventilation. Local exhaust ventilation may be necessary.			
		Keep containers covered	d whenever possible.		
Respiratory Protection		When respiratory protect	tion is required, use a N	IIOSH approved air-	
		purifying respirator equip	ng respirator equipped with an organic vapor canister. For		
		emergency and other co	nditions where exposur	e limits may be greatly	
		exceeded, use an appro-	ved positive-pressure, s	self-contained breathing	
		apparatus or positive-pre			
		supply.			
			Wear protective gloves and clothing. Use solvent-resistant apron &		
		boots, if needed.			
Eye Protection		Use safety glasses with side shields or, preferably, chemical goggles.			

9. Physical and Chemical Properties		
Boiling Point	367°F (186°C)	
Specific Gravity	1.01	
% Volatiles	85%	
Solubility in Water	Slightly soluble (3.4ml/100ml)	
pH	No information available	
Odor	Mild, characteristic odor	
Form	Liquid	
Color	Yellow	
VOC	7.49 lbs/gal coating	

10. Stability and Reactivity			
Chemical Stability	Stable under normal storage conditions.		
Conditions to Avoid	Keep product away from heat, sparks, static electricity, and open flame.		
Incompatibility	Strong bases. Strong oxidizing agents.		
Hazardous Decomposition Products	Burning can produce carbon monoxide, carbon dioxide, & nitrogen		
	oxides when heated to decomposition.		
Hazardous Polymerization	Will not occur		

11. Toxicological Information		
Results of component toxicity test performed:		
Data for Butyl Lactate	Acute Toxicity Data: Oral rat LD50: >5000 mg/kg;	
(CAS 138-22-7)	Subcutaneous rat LD50: 12000 mg/kg;	
Skin rabbit LD50: >5000 mg/kg;		
	Draize test, rabbit, skin: 500 mg/24H Moderate	
	Inhalation, rat LC50:>5140 mg/kg	
Data for Solvent Yellow 82	Acute Toxicity Data: Oral rat LD50: >10000 mg/kg;	

12. Ecological Information	1		
The following properties are ESTIMATED fro	m the components of the	preparations.	
Potential Toxicity:			
Toxicity to Danio rerio (LC50):	75 mg/L /96 Hr		
Toxicity to Daphnia magna (ÉC50): 320 mg/L /48Hr			
Persistence and degradability		ND	
Chemical Oxygen Demand (COD)		1.97lb O ₂ /lb	
Biochemical Oxygen Demand (BOD)		ND	
Chemical Fate Information		ND	

13. Disposal Considerations
Liquid material should be disposed as flammable waste. Note that Federal, State and local laws governing disposal of materials can differ. Ensure proper disposal compliance with proper authorities before disposal.
Contact a licensed professional waste disposal service to dispose of large quantities of this material

14. Transport Information		
Proper Shipping Name	Combustible Liquid, N.O.S.	
UN No.	NA1993	
IATA Class	Not Regulated	
Packing Group		

15. Regulatory Information		
U.S. Federal Regulations		
TSCA Section 8 (b) Inventory	All components are listed on the TSCA Chemical Inventory	
OSHA	Hazardous by definition of Hazard Communications Standard (29CFR1910.1200)	
SARA Hazard Category	·	
SARA 302 Components	No listed components	
SARA 313 Components	No listed components	
SARA 311/312 Hazards	Acute Health Hazard, Chronic Health Hazard, Fire Hazard	
Clean Water Act	No listed components	

State Regulations	
Massachusetts Right To Know	Butyl Lactate
Components	
Pennsylvania Right To Know	Butyl Lactate
Components	
New Jersey Right To Know Components	Butyl Lactate
California Proposition 65 Components	This product does not contain any chemical known to the State of
	California to cause cancer or reproductive harm.

16. Other Information	
HMIS	
H – 2	
F-2	
R – 0	
PPE – B	

The information in this material safety data sheet should be provided to all who will use, handle, store, transport, or otherwise be exposed to this product. This information has been prepared for the guidance of plant engineering, operations & management, and for persons working with or handling this product. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions but does not purport to be all inclusive. Horizons Incorporated shall not be held liable for any damage resulting from handling or from contact with the above product.